

## DustMagnet™ Performance & specifications

Product dimensions (H x W x D)

Product weight (including filter)

<sup>1</sup>According to ANSI/AHAM AC-1-2015. <sup>2</sup>Sound pressure according to GB18801 and GB4214.1. <sup>3</sup>According to GB/T18801-2015.



520 x 220 x 220 mm

4.5 kg (9.9 lbs)



520 x 220 x 220 mm

4.5 kg (9.9 lbs)



650 x 290 x 290 mm

YesNo

6.8 kg (14.9 lbs)

Model	5210i	5240i	5440i
Room size (4.8 air changes per hour)	20 m² (212 ft²)	20 m² (212 ft²)	33 m² (357 ft²)
Room size (2 air changes per hour)	48 m² (517 ft²)	48 m² (517 ft²)	79 m² (850 ft²)
Blueair recommends 4.8 air changes per hour according to AHAM.			
Claimed product performance			
Filtration Technology	HEPASilent™	HEPASilent™	HEPASilent™
Smoke CADR <sup>1</sup>	232 m³/h (137 cfm)	232 m <sup>3</sup> /h (137 cfm)	391 m <sup>3</sup> /h (230 cfm)
Dust CADR <sup>1</sup>	226 m³/h (133 cfm)	226 m³/h (133 cfm)	408 m³/h (240 cfm)
Pollen CADR <sup>1</sup>	238 m <sup>3</sup> /h (140 cfm)	238 m <sup>3</sup> /h (140 cfm)	433 m <sup>3</sup> /h (255 cfm)
Product			
Sound level <sup>2</sup> – High	47 dB(A)	47 dB(A)	49 dB(A)
- Low	23 dB(A)	23 dB(A)	30 dB(A)
Power consumption <sup>3</sup> - High	22 W	22 W	42 W
- Low	4 W	4 W	7 W
Clean Air Distribution	Side Flow	Side Flow	Side Flow
Energy Efficiency (particle CADR/W)	10.5	10.5	9
Filters			
Filter type	ComboFilter 5200	ComboFilter 5200	ComboFilter 5400
Prefilters	Charged & Cleanable	Charged & Cleanable	Charged & Cleanable
Main Replacement Filters	Double (S)	Double (S)	Double (M)
Number of filters	2	2	2
Filter Lifetime	Up to 1 year	Up to 1 year	Up to 1 year
Connectivity / sensors			
Blueair app (Wi-Fi connected)	•	•	•
Auto Mode	•	•	•
Particle sensor	LED	LED	LED
User Interface			
Material & finishing	Plastic, sophisticated matte finish	Plastic, sophisticated matte finish, fabric	Plastic, sophisticated matte finish, fabric
Air quality indicator light bar	•	•	•
Dimensions / weight			